

```
//
// Do any local configuration here
//

// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";
zone "devlan.net" {
    type forward;
    forward only;
    forwarders { 10.3.1.12; };
};

// Reverse DNS for Devlan (10.3.0.0)
zone "3.10.in-addr.arpa." {
    type forward;
    forward only;
    forwarders { 10.3.1.12; };
};

// Reverse DNS for Devlan (10.2.0.0)
zone "2.10.in-addr.arpa." {
    type forward;
    forward only;
    forwarders { 10.3.1.12; };
};

zone "testrange.local" {
    type forward;
    forward only;
    forwarders { 10.9.8.21; };
};

// Reverse DNS for TestRange (10.9.8.0)
zone "8.9.10.in-addr.arpa." {
    type forward;
    forward only;
    forwarders { 10.9.8.21; };
};

zone "loki.lab" {
    type forward;
    forward only;
    forwarders { 10.0.0.12; };
};

// Override query for vcenter host
zone "vcenter.loki.lab" {
    type master;
    file "/etc/bind/db.loki.lab"; //Zone file path
};

// Override query for esxi-1.loki.lab host
zone "esxi-1.loki.lab" {
    type master;
    file "/etc/bind/db.loki.lab"; //Zone file path
};

// Override query for esxi-2.loki.lab host
```

```
zone "esxi-2.loki.lab" {
    type master;
    file "/etc/bind/db.loki.lab"; //Zone file path
};

// Override query for esxi-3.loki.lab host
zone "esxi-3.loki.lab" {
    type master;
    file "/etc/bind/db.loki.lab"; //Zone file path
};

// Override query for esxi-4.loki.lab host
zone "esxi-4.loki.lab" {
    type master;
    file "/etc/bind/db.loki.lab"; //Zone file path
};

// Reverse DNS for Loki.lab (10.9.9.0)
zone "9.9.10.in-addr.arpa." {
    type forward;
    forward only;
    forwarders { 10.0.0.12; };
};

// Reverse DNS for Loki.lab (10.0.0.0)
zone "0.10.in-addr.arpa." {
    type forward;
    forward only;
    forwarders { 10.0.0.12; };
};
```